

CASIT DICARLO CESARE RAMELLA & C. SNC
 Strada Pietra Alta 1 – 10040 CASELETTE (TO) Italy
 Tel. 011-9688230 / 170 Fax 011-9688363
 Partita IVA/COD.FISC. 00506590017
 Cod. Destinataro: **BA6ET11**
 Trib. Torino N.654/62 - C. C.I.A.A. 333122
 M: T0024777 – COD. EORI: IT00506590017
 Sito www.casit-italy.com E-Mail info@casit.it



Italian Openings & Automation
 SINCE 1954



Cancelli Automatici - **Shed** - Infixi Telecomandati

MADE IN ITALY

YDRA 270

INTENSIVE USE

DATI TECNICI | DATA SHEETS | FICHE TECHNIQUE | DATOS TECNICOS

Tensione alimentazione Power supply Tension alimentation Tensione de alimentaciòn**	230 Vac 50 60 Hz
Motore elettrico Electric motor Moteur électrique Motor electrico (rpm)	1400
Corrente Current Courant Corriente (A)	1 A
Potenza motore Motor power Puissance moteur Potencia motore (W)	250 W
Termoprotezione Thermal protection Protection thermique Protección térmica	150 °
Condensatore Capacitor Condensateur Condensador	10 µf
Forza di spinta Thrust forcer Force de poussé Fuerza de empuje (max)	650 daNm
Corsa stelo Extension stem Etendue tige Recorrido vastago	270 mm
Velocità lineare stelo Speed linear stem Vitesse tige linéaire Velocidad lineal vastago	1,3 cm sec
Rallentamento corsa idraulico Hydraulic slowdown Rallentissement hydraulique Parada suave hidraulico	
Portata pompa Pump capacity Capacité pompe Capacidad bomba	1 l min
Olio Oil Huile Aceite	Total 52 AT 42
Temp. di funzionamento Operating temp. Temp. de fonctionnement Temp. ambiente	-20° C +70° C
Grado di protezione Class protection Classe de protection Grado de protección	IP 55
Blocco anta Swing lock Blocage portail Bloqueo hoja	apertura - chiusura
Peso Weight Poids Peso	9 Kg
Dimensioni Dimensions Dimensions moteur Medidas (L x P x H) mm	1090 x 99 x 123



CASIT DI CARLO CESARE RAMELLA & C. SNC
 Strada Pietra Alta 1 – 10040 CASELETTE (TO) Italy
 Tel. 011-9688230 / 170 Fax 011-9688363
 Partita IVA/COD.FISC. 00506590017
 Cod. Destinataro: **BA6ET11**
 Trib. Torino N.654/62 - C.C.I.A.A. 333122
 M: T0024777 – COD. EORI: IT00506590017
 Sito www.casit-italy.com E-Mail info@casit.it



Italian Openings & Automation
 SINCE 1954



Cancelli Automatici - **Shed** - Infixi Telecomandati

MADE IN ITALY

YDRA 390

INTENSIVE USE

DATI TECNICI | DATA SHEETS | FICHE TECHNIQUE | DATOS TECNICOS

Tensione alimentazione Power supply Tension alimentation Tensione de alimentaciòn**	230 Vac 50 60 Hz
Motore elettrico Electric motor Moteur électrique Motor electrico (rpm)	1400
Corrente Current Courant Corriente (A)	1,9 A
Potenza motore Motor power Puissance moteur Potencia motore (W)	350 W
Termoprotezione Thermal protection Protection thermique Protección térmica	150 °
Condensatore Capacitor Condensateur Condensador	10 µf
Forza di spinta Thrust forcer Force de poussé Fuerza de empuje (max)	780 daNm
Corsa stelo Extension stem Etendue tige Recorrido vastago	390 mm
Velocità lineare stelo Speed linear stem Vitesse tige linéaire Velocidad lineal vastago	1,3 cm sec
Rallentamento corsa idraulico Hydraulic slowdown Rallentissement hydraulique Parada suave hidraulico	
Portata pompa Pump capacity Capacité pompe Capacidad bomba	1 l min
Olio Oil Huile Aceite	Total 52 AT 42
Temp. di funzionamento Operating temp. Temp. de fonctionnement Temp. ambiente	-20° C +70° C
Grado di protezione Class protection Classe de protection Grado de protección	IP 55
Blocco anta Swing lock Blocage portail Bloqueo hoja	apertura - chiusura
Peso Weight Poids Peso	10 Kg
Dimensioni Dimensions Dimensions moteur Medidas (L x P x H) mm	1330 x 99 x 123

